

# KONTO



Konto



# KONTO

With a natural, rough look, Konto acoustic products are made in Finland from surface peat and have excellent sound absorption properties. In addition to the standard colours and sizes, the material can be cut into different shapes and painted in the colours specified by the customer. Konto panels surface also allows you to print on it.

The material is surface peat with a 20% polyester binder. Four panel strength options are available: 20, 30, 40 and 50 mm. Sound absorption class when directly fixed to the wall D - A / EN ISO 11654, depending on

the strength of the material. ratings when directly fixed to the wall D - A / EN ISO 11654, depending on the strength of the material. An air gap behind the panels increases the damping effect. The product has an indoor climate rating of M1, which means that the material or paint does not emit any emissions or odours that are harmful to health. The basic quality has a fire classification of class E. A more fire-safe quality (B-grade) is also available, classified B-s3-d0. The material has good moisture tolerance and is mildew resistant (pH acidic).

The panels have a natural, living surface with variations in colour and smoothness. There may also be differences in colour between series painted at different times.

## STANDARD COLOURS

- White
- Black
- Red M326
- Grey 1933
- Turquoise S2055

Custom colour specifications: RAL, NCS or Tikkurila

## STANDARD SIZES

- 594 × 594 mm and 1194 × 594 mm
- The maximum size of a single panel is 1200 × 2400 mm.
- The panels can also be made into double-sided elements that can be suspended from the ceiling.

## INSTALLATION AND MAINTENANCE

Konto acoustic panels are lightweight and easy to install, e.g. with an adhesive for acoustic panels, or with Velcro.

With mounting profiles, screw fixing is also possible.

The surface can be lightly vacuumed with a soft nozzle.

Eventually, the product can be recycled as energy waste.

