

SOFTEN, GROOVED PATTERNED PANELS



SOFTEN, GROOVED PATTERNED PANELS

The surface of the felt panels can be grooved to create a pattern. The size of the panel can be freely determined within the maximum size of the felt board.. The pattern can be designed to continue naturally from panel to panel. The design can be a full wall covering or individual panels.

The computer-controlled cutter creates the patterns planned for each project. The patterns can consist of diagonal or gently curved shapes. However, there are some limitations to cutting, which are useful to go through before proceeding with the design. We are happy to give you more information and help you to design a suitable pattern!

The grooved panels can be made in the standard felt colours. The single-colour finish is subtle in style.

The panels can be fixed directly to the wall, providing a lightly sound-absorbing surface. If you want a particularly good sound absorption effect from your surface, add e.g. 25 mm of acoustic infill behind the panel.



- material 100% PES (made from recycled PET bottles)
- max. size of the felt panel L 1250 x H 3000 mm
- felt panel thickness 8 mm (other thicknesses also possible)
- standard colours light grey, dark grey, white or black
- groove shape is V, width at the surface 6 - 10 mm
- edge trims are also possible
- optional acoustic infill 25 mm on the wall with bracing, or pre-fixed to the panel
- indoor climate classification M1 (felt surface & infill)
- fire classification of the felt surface B-s1,d0 / EN 13501-1
- adhesive, nailing, velcro or screws for installation.
- can be cut to size/cut out on site with a carpet knife.
- delivery in approx. 4 weeks